



One Corporate Drive, Suite 106
Bedford, PA 15522-7983
(814) 623-8125
bedfordreinforced.com

JOB REFERENCE NAME/NUMBER:

SCOPE OF WORK

Handrail

Drawing Number _____

Ladder

Drawing Number _____

Platform

Drawing Number _____

Stairs

Drawing Number _____

Stair Tower

Drawing Number _____

Grating

Drawing Number _____

GENERAL DESIGN CRITERIA

Design Load: 100 psf or less (BRP Standard) > 100 psf
Chemical Environment: No Yes (if yes, please list:) _____
Temperature Range: < 150°F 150°F - 200°F > 200°F

SPECIAL REQUIREMENTS

Will engineering calculations be required? Yes No
Will PE stamp/seal be required? Yes No If yes, for what state or province? _____
Will the material need to be certified for potable water/NFS 61? Yes No
Will additional UV protection be required? Yes No

PLATFORMS/STRUCTURAL REQUIREMENTS

FRP STRUCTURAL SHAPES AND PLATE (See BRP PROForms® & PROPlate® Brochure and Platform Spec Sheet)

Resin Series: Polyester Dark Gray Vinylester Beige

LADDER REQUIREMENTS

LADDER (See BRP Ladder Brochure and Ladder Spec Sheet)

Resin Series: Polyester Fire Retardant Yellow Vinylester Fire Retardant Yellow

Ladder Cage Required? Yes No



HANDRAIL REQUIREMENTS

HANDRAIL (See BRP [Handrail Spec Sheet](#))

Resin Series:	Polyester Fire Retardant Yellow	Vinylester Yellow
Handrail Series:	Standard Duty	Heavy Duty

PULTRUDED GRATING REQUIREMENTS

PULTRUDED GRATING & TREAD (See BRP [PROGrid®](#) & [PROGrate®](#) Brochure)

Thickness:	Open Area:		
Resin Series:	Polyester Fire Retardant	Vinylester Fire Retardant	
Color:	Light Gray	Dark Gray	Yellow
Design Load:	100 psf or less (BRP Standard)	> 100 psf	
Deflection Limits:	< .25" (BRP Standard)	Other (please advise:) _____	
Hold-Down Clips:	Yes	No	

MOLDED GRATING REQUIREMENTS

MOLDED GRATING & TREAD (See BRP [PROGrid®](#) & [PROGrate®](#) Brochure)

Resin Series:	GP/FR General Purpose Fire Retardant Polyester	IFR Premium Isophthalic Fire Retardant Polyester	VFR Fire Retardant Vinylester
Thickness:	Grid Pattern:		
Grating Surface:	Gritted	Meniscus	
Design Load:	100 psf or less (BRP Standard)	> 100 psf	
Deflection Limits:	< .25" (BRP Standard)	Other (please advise:) _____	
Color:			
Hold-Down Clips:	Yes	No	

ADDITIONAL NOTES