



SAFETY DATA SHEET

REQUIRED BY OSHA'S 29 CFR 1910.1200

Date of Preparation or Revision: January 23, 2017

Section 1 – Identification

| | |
|--|---|
| MANUFACTURER'S NAME: Bedford Reinforced Plastics, Inc. | EMERGENCY PHONE #: 814-623-8125 |
| ADDRESS: 1 Corporate Drive, Suite 106, Bedford, PA 15522 | |
| PRODUCT DESCRIPTION: Pultruded Fiberglass Thermoset Polyester/FR Polyester | TRADE NAME: PROForms® |
| Recommended Use: | Restrictions on Use: |

Section 2 – Hazard(s) Identification

| | | |
|---|-------------------------------|--|
| BOILING POINT: N/A | MELTING POINT: N/A | VAPOR DENSITY (AIR 1): N/A |
| SPECIFIC GRAVITY: (H ₂ O = 1) 1.60 - 2.00 | VAPOR PRESSURE: (mmHg) N/A | EVAPORATION RATE: (Butyl Acetate = 1) N/A |
| APPEARANCE AND ODOR: Various shapes and colors, slight plastic odor | | |

Section 3 – Composition/Information on Ingredients

| COMPONENTS | PERCENT | PEL ppm-mg/M(3) | CAS # |
|------------------------------|---------|---|------------|
| Polyester Resin, Polymerized | 30-50 | N/A | |
| Fiberglass | 50-70 | Total nuisance dust 15mg/m ³ | 65997-17-3 |
| | | Respirable nuisance dust 5mg/m ³ | |

Section 4 – First-Aid Measures

| | |
|-------------------------------------|--|
| ROUTE(s) OF ENTRY: | Inhalation, eyes, contact with skin |
| SIGNS AND SYMPTOMS OF EXPOSURE: | Inhalation - dry, scratchy throat; Irritation to skin |
| EMERGENCY AND FIRST AID PROCEDURES: | Inhalation - remove to fresh air; Eyes - flush with approved eye wash; Skin - wash with soap & water |



Section 5 – Fire-Fighting Measures

| | |
|--|-----------------------|
| FLASH POINT: N/A | FLAMMABLE LIMITS: N/A |
| EXTINGUISHING MEDIA: Water, CO2, Dry Chemical, Foam | |
| SPECIAL FIREFIGHTING PROCEDURES: Self-contained breathing apparatus, avoid breathing fumes and smoke from fire | |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: None | |

Section 6 – Handling and Storage

| |
|---|
| WASTE DISPOSAL METHOD: Abide by local, state and federal laws. Not considered a hazardous waste. |
| PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Use dust collector when sawing and routing. Gloves for handling comfort. |
| OTHER PRECAUTIONS: |

Section 7 – Exposure Controls/Personal Protection

| | |
|--|--------------------------------|
| RESPIRATION PROTECTION (Specify Type): Dust mask, Dust collector | |
| VENTILLATION: Local exhaust | MECHANICAL: (General) |
| PROTECTIVE GLOVES: Leather | EYE PROTECTION: Safety glasses |
| OTHER PROTECTIVE EQUIPMENT OR CLOTHING: | |

Section 8 – Stability and Reactivity

| | | |
|---|------------------|--------------------------|
| STABILITY | | CONDITIONS TO AVOID: |
| Stable: X | Unstable: | Extreme high temperature |
| INCOMPATIBILITY (Materials to avoid): N/A | | |
| HAZARDOUS DECOMPOSITION OR BYPRODUCT: N/A | | |
| HAZARDOUS POLYMERIZATION | | CONDITIONS TO AVOID: |
| May Occur: | May Not Occur: X | |

THE MATERIAL SAFETY DATA SHEET IS SOLELY FOR DETAILING, REFLECTING, AND ANALYZING BY THE CUSTOMER. BEDFORD REINFORCED PLASTICS, INC., GRANTS NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR ACCURACY OR COMPLETENESS OF DATA CONTAINED THEREIN.